

Printing date 08.11.2019 Version number 9 Revision: 30.10.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: DINITROL 3125 HS
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Anticorrosion additive
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

DINOL GmbH Pyrmonter Str. 76 D-32676 Lügde Tel: +49 5281 9829 80

Fax: +49 5281 9829 860 E-mail: msds@dinol.com

- · Further information obtainable from: Research & Development
- · 1.4 Emergency telephone number:

Giftnotruf Berlin +49(0)30 30686 700 Beratung in Deutsch und Englisch.

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02

GHS07

- · Signal word Warning
- · Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated heavy

· Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P243 Take precautionary measures against static discharge.

(Contd. on page 2)



Printing date 08.11.2019 Version number 9 Revision: 30.10.2019

Trade name: DINITROL 3125 HS

(Contd. of page 1)

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

· 2.3 Other hazards

The petroleum naphtha / petroleum distillate / lubricating oil meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w) DMSO extract (IP 346)).

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with additions.

· Dangerous components:		
CAS: 64742-48-9	Naphtha (petroleum), hydrotreated heavy	25-<50%
EC number: 919-857-5	🚳 Flam. Liq. 3, H226; 🚯 Asp. Tox. 1, H304; 🕦 STOT SE 3, H336	
Reg.nr.: 01-2119463258-33	· · · · · · · · · · · · · · · · · · ·	
CAS: 25619-56-1	Barium alkylnaphtalenesulfonate	1-<5%
EC number: 939-718-2	① Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Irrit. 2, H315	
Reg.nr.: 01-2119980986-14		

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After skin contact:

Immediately rinse with water.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Wash out mouth with water. Contact a physician.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)



Printing date 08.11.2019 Version number 9 Revision: 30.10.2019

Trade name: DINITROL 3125 HS

(Contd. of page 2)

· 5.3 Advice for firefighters

· Protective equipment: Mount respiratory protective device.

· Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Prevent seepage into sewage system, workpits and cellars.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Use only in well ventilated areas.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage.
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs		
CAS: 6474	12-48-9 Naphtha (petroleum), hydrotreated heavy	y
Oral	Long-term - systemic effects, general population	125 mg/kg bw/day (General Population)
Dermal	Long-term - systemic effects, worker	208 mg/kg bw/day (Worker)
	Long-term - systemic effects, general population	125 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects, worker	871 mg/m3 (Worker)
	Long-term - systemic effects, general population	185 mg/m3 (General Population)
		(Contd. on pag

Contd. on page 4



Printing date 08.11.2019 Version number 9 Revision: 30.10.2019

Trade name: DINITROL 3125 HS

(Contd. of page 3)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.



Filter A

· Protection of hands:



Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber

Recommended thickness of the material: ≥ 0.12 mm

- · Penetration time of glove material
- > 480 min

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Dispersion
Colour: Beige

Odour: Characteristic
Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined. Initial boiling point and boiling range: 130 °C

• Flash point: 37 °C (DIN 53213)

(Contd. on page 5)



Printing date 08.11.2019 Version number 9 Revision: 30.10.2019

Trade name: DINITROL 3125 HS

	(Contd. of page
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	>200 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air vapour mixtures are possible.
· Explosion limits:	
Lower:	0.6 Vol %
Upper:	7 Vol %
· Vapour pressure At 20 °C:	3 hPa
· Density At 20 °C:	0.98 g/cm³ (DIN 51757)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic At 20 °C:	55 s (DIN 53211/4)
· Solvent content:	
Organic solvents:	28.1 %
Solids content:	68.0 % (DIN 53216)
· 9.2 Other information	No further relevant information available.
· VOC (EU):	28.12 %
· <i>VOC (EU):</i>	275.6 g/l
· VOCV:	28.12 %

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 6)



Printing date 08.11.2019 Version number 9 Revision: 30.10.2019

Trade name: DINITROL 3125 HS

(Contd. of page 5)

· LD/LC50 values relevant for classification:		
ATE (Acute Toxicity Estimates)		
Oral	LD50	>15,432-18,519 mg/kg
Inhalative	LC50/4 h	>46.3-55.6 mg/l

CAS: 64742-48-9 Naphtha (petroleum), hydrotreated heavy

Oral	LD50	>5,000 mg/kg (RAT)
		>5,000 mg/kg (RABBIT)
Inhalative	LC50/4 h	5,000 mg/l (RAT)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information: No further relevant information available.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Dispose of as dangerous waste.

· European waste catalogue	
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
HP3	Flammable

(Contd. on page 7)



Printing date 08.11.2019 Version number 9 Revision: 30.10.2019

Trade name: DINITROL 3125 HS

(Contd. of page 6)

HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport informat	non
14.1 UN-Number ADR/RID/ADN, IMDG, IATA	UN1139
14.2 UN proper shipping name ADR/RID/ADN IMDG, IATA	1139 COATING SOLUTION COATING SOLUTION
14.3 Transport hazard class(es)	
ADR/RID/ADN, IMDG, IATA	
Class Label	3 Flammable liquids. 3
14.4 Packing group ADR/RID/ADN, IMDG, IATA	III
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user Danger code (Kemler): EMS Number: Stowage Category	Warning: Flammable liquids. 30 F-E, <u>S-E</u> A
14.7 Transport in bulk according to Anno Marpol and the IBC Code	e x II of Not applicable.
Transport/Additional information:	
ADR/RID/ADN Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category Tunnel restriction code	3 D/E
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN ''Model Regulation'':	UN 1139 COATING SOLUTION, 3, III



Printing date 08.11.2019 Version number 9 Revision: 30.10.2019

Trade name: DINITROL 3125 HS

(Contd. of page 7)

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02

GHS07

- · Signal word Warning
- · Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated heavy

· Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P243 Take precautionary measures against static discharge.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:
- · Technical instructions (air):

Class	Share in %
NK	28.1

- · Waterhazard class: Water hazard class 3 (Self-assessment): extremely hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

(Contd. on page 9)



Printing date 08.11.2019 Version number 9 Revision: 30.10.2019

Trade name: DINITROL 3125 HS

(Contd. of page 8)

H315 Causes skin irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

- · Department issuing SDS: Research & Development
- · Contact: Kontakt: msds@dinol.com oder Tel.: 0049 (0)5281 982 980
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

* * Data compared to the previous version altered.