

Printing date 28.07.2015 Version number 15 Revision: 28.07.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: DINITROL 3641E

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Anticorrosion additive
- · 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

DINOL GmbH Pyrmonter Str. 76 D-32676 Lügde Tel: ±49 5281 9829

Tel: +49 5281 9829 80 Fax: +49 5281 9829 860 E-mail: msds@dinol.com

- · Further information obtainable from: Research & Development
- · 1.4 Emergency telephone number:

Giftnotruf Berlin +49(0)30 30686 790 Beratung in Deutsch und Englisch.

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02

Flam. Liq. 3 H226 Flammable liquid and vapour.



STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS07

- · Signal word Warning
- · Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated heavy Naphtha (petroleum), hydrotreated heavy

· Hazard statements

H226 Flammable liquid and vapour. H336 May cause drowsiness or dizziness.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P243 Take precautionary measures against static discharge.
 P280 Wear protective gloves/protective clothing/eye protection.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

(Contd. on page 2)



Printing date 28.07.2015 Version number 15 Revision: 28.07.2015

Trade name: DINITROL 3641E

(Contd. of page 1)

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains Calcium Sulfonate. May produce an allergic reaction.

· 2.3 Other hazards

The petroleum naphtha / petroleum distillate / lubricating oil meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w) DMSO extract (IP 346)).

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with additions.

· Dangerous components:		
CAS: 64742-48-9	Naphtha (petroleum), hydrotreated heavy	10-<25%
EC number: 919-857-5	♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ STOT SE 3, H336	
Reg.nr.: 01-2119463258-33	v i v	
CAS: 64742-48-9	Naphtha (petroleum), hydrotreated heavy	1-<5%
EINECS: 265-150-3	Naphtha (petroleum), hydrotreated heavy This is a superscript of the	
CAS: 61789-86-4	Calcium Sulfonate	1-<5%
	🕠 Skin Sens. 1B, H317	

[·] Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents:

Water

Water with full jet

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Mount respiratory protective device.

(Contd. on page 3)



Printing date 28.07.2015 Version number 15 Revision: 28.07.2015

Trade name: DINITROL 3641E

(Contd. of page 2)

· Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Avoid contact with skin, eyes and clothes.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Use only in well ventilated areas.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs	· DNELs		
64742-48-	64742-48-9 Naphtha (petroleum), hydrotreated heavy		
Oral	Long-term - systemic effects, general population	125 mg/kg bw/day (General Population)	
Dermal	Long-term - systemic effects, general population	125 mg/kg bw/day (General population)	
	Long-term - systemic effects, worker	208 mg/kg bw/day (Worker)	
Inhalative	Long-term - systemic effects, general population	185 mg/m3 (General Population)	
	Long-term - systemic effects, worker	871 mg/m3 (Worker)	

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

(Contd. on page 4)



Printing date 28.07.2015 Version number 15 Revision: 28.07.2015

Trade name: DINITROL 3641E

(Contd. of page 3)

Do not inhale gases / fumes / aerosols. · Respiratory protection: Not required.

· Protection of hands:



Protective gloves

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber

Recommended thickness of the material: ≥ 0.12 mm

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

SECTION 9: P.	hysical and	chemical	propert	ties

. Q	1 Informatio	n on hasi	c nhysical	and cher	nical properties
٠,٠,٠	a mijormuno	n on vasi	ı pnysicui	ини спен	nicai properiies

· General Information

· Appearance: Form:

Viscous Colour: Brown · Odour:

Characteristic Not determined. · Odour threshold:

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined. 130 °C Boiling point/Boiling range:

41 °C (DIN 53213) · Flash point:

· Flammability (solid, gaseous): Not applicable.

> 200 °C · Ignition temperature:

· Decomposition temperature: Not determined.

· Self-igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapour

mixtures are possible.

· Explosion limits:

0.6 Vol % Lower: 7.0 Vol % Upper:

· Vapour pressure At 20 °C: 3 hPa

· Density At 20 °C: 1.04 g/cm³ (DIN 51757)

· Relative density Not determined.

(Contd. on page 5)



Version number 15 Printing date 28.07.2015 Revision: 28.07.2015

Trade name: DINITROL 3641E

		(Contd. of page
· Vapour density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol	/water): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic At 20 °C:	47 s (DIN 53211/4)	
· Solvent content:		
Organic solvents:	25.1 %	
Solids content:	74.0 % (DIN 53216)	
· 9.2 Other information	No further relevant information available.	
· VOC (EU):	25.08 %	
\cdot VOC (EU) :	260.8 g/l	
· VOCV:	25.08 %	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

	1100000		
ſ	· LD/LC50 values relevant for classification:		
Ī	64742-48-9 Naphtha (petroleum), hydrotreated heavy		
ľ	Oral	LD50	>5000 mg/kg (RAT)
	Dermal	LD50	>5000 mg/kg (RABBIT)
	Inhalative	LC50/4 h	> 4951 mg/l (RAT)
64742-48-9 Naphtha (petroleum), hydrotreated heavy		(petroleum), hydrotreated heavy	
ſ	Oral	LD50	>5000 mg/kg (RAT)
	Dermal	LD50	>3000 mg/kg (RAT)
-	Primary irritant offact		

- · Primary irritant effect:
- · Skin corrosion/irritation

Prolonged or repeated contact with skin may cause slight irritation and/or reddening.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information: No further relevant information available.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

· STOT-repeated exposure Based on available data, the classification criteria are not met.

(Contd. on page 6)



Printing date 28.07.2015 Version number 15 Revision: 28.07.2015

Trade name: DINITROL 3641E

(Contd. of page 5)

· Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- $\cdot \textbf{\textit{Aquatic toxicity:}} \ \textit{No further relevant information available}.$
- · 12.2 Persistence and degradability No further relevant information available.
- $\cdot \ \textbf{12.3 Bioaccumulative potential} \ \textit{No further relevant information available}.$
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Dispose of as dangerous waste.

· European	· European waste catalogue			
	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS			
08 01 00	wastes from MFSU and removal of paint and varnish			
08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances			

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

- · 14.1 UN-Number
- · ADR, IMDG, IATA

· 14.2 UN proper shipping name

 $\cdot ADR$ 1139 COATING SOLUTION, special provision 640E

UN1139

· IMDG, IATA **COATING SOLUTION**

- · 14.3 Transport hazard class(es)
- · ADR, IMDG, IATA



· Class 3 Flammable liquids.

· Label

(Contd. on page 7)



Printing date 28.07.2015 Version number 15 Revision: 28.07.2015

Trade name: DINITROL 3641E

	(Contd. of page
14.4 Packing group	
ADR, IMDG, IATA	III
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	30
EMS Number:	F-E, <u>S-E</u>
14.7 Transport in bulk according to An	nex II of
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN1139, COATING SOLUTION, special provision 640
	3, III

SECTION 15: Regulatory information

- \cdot 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02

GHS07

- · Signal word Warning
- · Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated heavy Naphtha (petroleum), hydrotreated heavy

· Hazard statements

H226 Flammable liquid and vapour. H336 May cause drowsiness or dizziness.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P243 Take precautionary measures against static discharge.
P280 Wear protective gloves/protective clothing/eye protection.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

(Contd. on page 8)



Printing date 28.07.2015 Version number 15 Revision: 28.07.2015

Trade name: DINITROL 3641E

(Contd. of page 7)

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Directive 2012/18/EU

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · National regulations:
- · Technical instructions (air):

Class	Share in %
NK	25.1

- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

- · Department issuing MSDS: Research & Development
- · Contact: Kontakt: msds@dinol.com oder Tel.: 0049 (0)5281 982 980
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids, Hazard Category 3 Skin Sens. 1B: Sensitisation - Skin, Hazard Category 1B

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

 $\cdot *$ Data compared to the previous version altered.

GB