

Safety Data Sheet

according to Regulation (EC) No 1907/2006

DINITROL 445 Droehnex Black

Print date: 08.04.2016

Product code: 5104

Page 2 of 16

**Hazard statements**

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe vapour/aerosol.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves and eye/face protection.
P308+P313	IF exposed or concerned: Get medical advice/attention.

Special labelling of certain mixtures

EUH208	Contains Fatty acids, C18-unsatd. , trimers, compds. with oleylamine, Fatty acids, tall-oil, compds. with oleylamine. May produce an allergic reaction.
--------	---

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

DINITROL 445 Droehnex Black

Print date: 08.04.2016

Product code: 5104

Page 3 of 16

Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification according to Directive 67/548/EEC	
Index No	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
REACH No		
920-750-0	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	10 - < 15 %
64742-49-0	F - Highly flammable, Xn - Harmful, Xi - Irritant, N - Dangerous for the environment R11-38-51-53-65-67	
649-328-00-1	Flam. Liq. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H336 H304 H411	
01-2119473851-33		
203-625-9	toluene	5 - < 10 %
108-88-3	Repr. Cat. 3, F - Highly flammable, Xn - Harmful, Xi - Irritant R11-63-48/20-65-38-67	
601-021-00-3	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H225 H361d H315 H336 H373 H304	
01-2119471310-51		
919-446-0	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	5 - < 10 %
64742-82-1	Xn - Harmful, N - Dangerous for the environment R10-48/20-51-53-65-66-67	
649-330-00-2	Flam. Liq. 3, STOT SE 3, STOT RE 1, Asp. Tox. 1, Aquatic Chronic 2; H226 H336 H372 H304 H411 EUH066	
01-2119458049-33		
215-535-7	xylene	5 - < 10 %
1330-20-7	Xn - Harmful, Xi - Irritant R10-20/21-38	
601-022-00-9	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H226 H312 H332 H315 H319 H335 H373 H304	
01-2119488216-32		
205-500-4	ethyl acetate	3 - < 5 %
141-78-6	F - Highly flammable, Xi - Irritant R11-36-66-67	
607-022-00-5	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066	
01-2119475103-46		
604-612-4	Fatty acids, C18-unsatd., trimers, compds. with oleylamine	0.1 - < 1 %
147900-93-4	T - Toxic, N - Dangerous for the environment R43-48/25-51-53	
	Skin Sens. 1B, STOT RE 1, Aquatic Chronic 2; H317 H372 H411	
288-315-1	Fatty acids, tall-oil, compds. with oleylamine	0.1 - < 1 %
85711-55-3	R43	
	Skin Sens. 1; H317	

Full text of R, H and EUH phrases: see section 16.

Further Information

Note: Each entry in the column EC number that begins with the number "9" is - until the publication the official registration number - one specified by ECHA provisional number for the substance. The above-mentioned substance(s) in this product is (are) identified by CAS number and indeed in Countries that are not subject to the REACH Regulation, or in a regulation which is not in accordance with new naming convention for hydrocarbons have been updated.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

If unconscious place in recovery position and seek medical advice.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

DINITROL 445 Droehnex Black

Print date: 08.04.2016

Product code: 5104

Page 4 of 16

Never give anything by mouth to an unconscious person or a person with cramps.
In all cases of doubt, or when symptoms persist, seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

After contact with skin

Change contaminated clothing.
Wash with plenty of water/Soap.
If skin irritation occurs: Get medical advice/attention.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of eye irritation consult an ophthalmologist.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).
Call a physician immediately.
Put victim at rest, cover with a blanket and keep warm.
Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Nausea, Drowsiness, Headache.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO₂), Extinguishing powder, Water fog.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Danger of serious damage to health by prolonged exposure.
Do not inhale explosion and combustion gases. Use appropriate respiratory protection.

5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation.
Wear personal protection equipment.
Avoid contact with skin, eyes and clothes.
Avoid breathing dust/fume/gas/mist/vapours/spray.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Prevent spread over a wide area (e.g. by containment or oil barriers).
Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).
Treat the recovered material as prescribed in the section on waste disposal.

according to Regulation (EC) No 1907/2006

DINITROL 445 Droehnex Black

Print date: 08.04.2016

Product code: 5104

Page 5 of 16

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Advice on protection against fire and explosion

Take precautionary measures against static discharges.

Keep away from sources of ignition. - No smoking.

Vapours are heavier than air and will spread at floor level.

Vapours may form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Keep container dry.

Keep away from heat. Protect against direct sunlight.

Advice on storage compatibility

Do not store together with: Oxidizing agents. Strong acid, strong alkalis

7.3. Specific end use(s)

Anti-corrosive coating

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
141-78-6	Ethyl acetate	200	-	-	TWA (8 h)	WEL
		400	-	-	STEL (15 min)	WEL
546-93-0	Magnesite, respirable dust	-	4	-	TWA (8 h)	WEL
		-	-	-	STEL (15 min)	WEL
14807-96-6	Talc respirable dust	-	1	-	TWA (8 h)	WEL
		-	-	-	STEL (15 min)	WEL
108-88-3	Toluene	50	191	-	TWA (8 h)	WEL
		100	384	-	STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220	-	TWA (8 h)	WEL
		100	441	-	STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid	650 mmol/mol	urine	Post shift

Safety Data Sheet

according to Regulation (EC) No 1907/2006

DINITROL 445 Droehnex Black

Print date: 08.04.2016

Product code: 5104

Page 6 of 16

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
64742-49-0	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics			
	Worker DNEL, long-term	dermal	systemic	773 mg/kg bw/day
	Worker DNEL, long-term	inhalation	systemic	2035 mg/m ³
	Consumer DNEL, long-term	dermal	systemic	699 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	699 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	608 mg/m ³
108-88-3	toluene			
	Worker DNEL, long-term	inhalation	systemic	192 mg/m ³
	Worker DNEL, acute	inhalation	systemic	384 mg/m ³
	Worker DNEL, acute	inhalation	local	384 mg/m ³
	Worker DNEL, long-term	inhalation	local	192 mg/m ³
	Worker DNEL, long-term	dermal	systemic	384 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	56,5 mg/m ³
	Consumer DNEL, acute	inhalation	systemic	226 mg/m ³
	Consumer DNEL, acute	inhalation	local	226 mg/m ³
	Consumer DNEL, long-term	inhalation	local	56,5 mg/m ³
	Consumer DNEL, long-term	dermal	systemic	226 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	8,13 mg/kg bw/day
64742-82-1	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)			
	Consumer DNEL, long-term	oral	systemic	26 mg/kg bw/day
	Worker DNEL, long-term	inhalation	systemic	330 mg/m ³
	Worker DNEL, long-term	dermal	systemic	44 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	71 mg/m ³
	Consumer DNEL, long-term	dermal	systemic	26 mg/kg bw/day
1330-20-7	xylene			
	Worker DNEL, long-term	dermal	systemic	108 mg/kg bw/day
	Worker DNEL, acute	inhalation	systemic	289 mg/m ³
	Worker DNEL, acute	inhalation	local	174 mg/m ³
	Worker DNEL, long-term	inhalation	systemic	77 mg/m ³
	Consumer DNEL, long-term	oral	systemic	1,6 mg/kg bw/day
	Consumer DNEL, long-term	dermal	systemic	108 mg/kg bw/day
	Consumer DNEL, acute	inhalation	systemic	174 mg/m ³

Safety Data Sheet

according to Regulation (EC) No 1907/2006

DINITROL 445 Droehnex Black

Print date: 08.04.2016

Product code: 5104

Page 7 of 16

Consumer DNEL, acute	inhalation	local	174 mg/m ³
Consumer DNEL, long-term	inhalation	systemic	14,8 mg/m ³
546-93-0	Magnesium carbonate		
Consumer DNEL, long-term	oral	systemic	7,23 mg/kg bw/day
Consumer DNEL, acute	oral	systemic	7,23 mg/kg bw/day
141-78-6	ethyl acetate		
Worker DNEL, long-term	inhalation	systemic	734 mg/m ³
Worker DNEL, acute	inhalation	systemic	1468 mg/m ³
Worker DNEL, long-term	inhalation	local	734 mg/m ³
Worker DNEL, acute	inhalation	local	1468 mg/m ³
Worker DNEL, long-term	dermal	systemic	63 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	367 mg/m ³
Consumer DNEL, acute	inhalation	systemic	734 mg/m ³
Consumer DNEL, long-term	dermal	systemic	37 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	4,5 mg/kg bw/day

according to Regulation (EC) No 1907/2006

DINITROL 445 Droehnex Black

Print date: 08.04.2016

Product code: 5104

Page 8 of 16

PNEC values

CAS No	Substance	Value
Environmental compartment		
108-88-3	toluene	
Freshwater		0,68 mg/l
Marine water		0,68 mg/l
Freshwater sediment		16,39 mg/kg
Marine sediment		16,39 mg/kg
Micro-organisms in sewage treatment plants (STP)		13,61 mg/l
Soil		2,89 mg/kg
1330-20-7	xylene	
Freshwater		0,327 mg/l
Marine water		0,327 mg/l
Freshwater sediment		12,46 mg/kg
Marine sediment		12,46 mg/kg
Soil		2,31 mg/kg
Micro-organisms in sewage treatment plants (STP)		6,58 mg/l
141-78-6	ethyl acetate	
Freshwater		0,24 mg/l
Marine water		0,024 mg/l
Freshwater sediment		1,15 mg/kg
Marine sediment		0,115 mg/kg
Secondary poisoning		0,20 mg/kg
Micro-organisms in sewage treatment plants (STP)		650 mg/l
Soil		0,148 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Protective and hygiene measures

Keep away from food, drink and animal feedingstuffs.

When using do not eat or drink.

Wash hands before breaks and after work.

Avoid contact with skin and eyes.

Remove contaminated, saturated clothing immediately.

Do not breathe gas/vapour/aerosol.

Eye/face protection

Eye glasses with side protection (DIN EN 166)

Hand protection

Tested protective gloves must be worn (DIN EN 374):

FKM (fluoro rubber), Breakthrough time (maximum wearing time): 480 min.

according to Regulation (EC) No 1907/2006

DINITROL 445 Droehnex Black

Print date: 08.04.2016

Product code: 5104

Page 9 of 16

PVA (Polyvinyl alcohol), Breakthrough time (maximum wearing time): 480 min.
 For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.
 Protective gloves have to be replaced at the first sign of deterioration.
 Protect skin by using skin protective cream.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.
 gas filtering equipment (EN 141)., Filter material/medium: A/P2

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
 Colour: black
 Odour: characteristic

Test method

pH-Value: not determined

Changes in the physical state

Melting point: not determined

Initial boiling point and boiling range: >77 °C

Flash point: -4 °C DIN 51755

Flammability

Solid: not applicable

Gas: not applicable

Explosive properties

not determined

Lower explosion limits: 0,8 vol. %

Upper explosion limits: 7,7 vol. %

Ignition temperature: >200 °C

Auto-ignition temperature

Solid: not applicable

Gas: not applicable

Decomposition temperature: not determined

Oxidizing properties

not determined

Vapour pressure:
 (at 20 °C) 61 hPa

Density (at 20 °C): 1,17 g/cm³ ISO 2811

Water solubility: insoluble

Solubility in other solvents

not determined

Partition coefficient: not determined

Viscosity / dynamic:
 (at 20 °C) 1000 mPa·s

Vapour density: not determined

Safety Data Sheet

according to Regulation (EC) No 1907/2006

DINITROL 445 Droehnex Black

Print date: 08.04.2016

Product code: 5104

Page 10 of 16

Evaporation rate:	not determined
Solvent separation test:	not determined
Solvent content:	43,6 %

9.2. Other information

Solid content:	56,4 %
----------------	--------

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from heat.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Carbon monoxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

DINITROL 445 Droehnex Black

Print date: 08.04.2016

Product code: 5104

Page 11 of 16

CAS No	Chemical name				
	Exposure route	Method	Dose	Species	Source
64742-49-0	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics				
	oral	LD50	>5000 mg/kg	Rat	
	dermal	LD50	>2800 mg/kg	Rabbit	
	inhalative vapour	LC50	>23,3 mg/l	Rat	
108-88-3	toluene				
	oral	LD50	>2000 mg/kg	Rat	
	dermal	LD50	12124 mg/kg	Rabbit	
	inhalative (4 h) vapour	LC50	28,1 mg/l	Rat	
64742-82-1	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)				
	oral	LD50	>150000 mg/kg	Rat	
	dermal	LD50	>3400 mg/kg	Rat	
1330-20-7	xylene				
	oral	LD50	4300 mg/kg	Rat	GESTIS
	dermal	LD50	>1700 mg/kg	Rabbit	GESTIS
	inhalative (4 h) vapour	LC50	21,7 mg/l	Rat	GESTIS
	inhalative aerosol	ATE	1,5 mg/l		
141-78-6	ethyl acetate				
	oral	LD50	4935 mg/kg	Rat	
	dermal	LD50	5000 mg/kg	Rabbit	
	inhalative (4 h) vapour	LC50	56 mg/l	Rat	

Irritation and corrosivity

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics), (toluene), (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)), (ethyl acetate)

Severe effects after repeated or prolonged exposure

May cause damage to organs through prolonged or repeated exposure. (toluene), (xylene)

Carcinogenic/mutagenic/toxic effects for reproduction

Suspected of damaging the unborn child. (toluene)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information
12.1. Toxicity

Safety Data Sheet

according to Regulation (EC) No 1907/2006

DINITROL 445 Droehnex Black

Print date: 08.04.2016

Product code: 5104

Page 12 of 16

CAS No	Chemical name					
	Aquatic toxicity	Method	Dose	[h] [d]	Species	Source
64742-49-0	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics					
	Acute fish toxicity	LC50	>13,4 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50	10-30 mg/l		Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50	3 mg/l	48 h	Daphnia magna (Big water flea)	
108-88-3	toluene					
	Acute fish toxicity	LC50	13 mg/l	96 h	Carassius auratus	IUCLID
	Acute algae toxicity	ErC50	12,0 mg/l	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50	11,5 mg/l	48 h	Daphnia magna (Big water flea)	
64742-82-1	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)					
	Acute fish toxicity	LC50	10 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50	4,6 mg/l	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50	10 mg/l	48 h	Daphnia magna (Big water flea)	
141-78-6	ethyl acetate					
	Acute fish toxicity	LC50	230 mg/l	96 h	Pimephales promelas (fathead minnow)	
	Acute algae toxicity	ErC50	3300 mg/l		Desmodesmus subspicatus.	48 h
	Acute crustacea toxicity	EC50	717 mg/l	48 h	Daphnia magna (Big water flea)	
	Acute bacteria toxicity		(2900 mg/l)		Pseudomonas putida	16 h

12.2. Persistence and degradability

There are no data available on the mixture itself.

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation				
64742-82-1	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)				
		74,7 %	28		
	Leicht biologisch abbaubar				
141-78-6	ethyl acetate				
	OECD 301D/ EEC 92/69/V, C.4-E	100 %	28		
	Readily biodegradable (according to OECD criteria).				

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
108-88-3	toluene	2,73
1330-20-7	xylene	3

Safety Data Sheet

according to Regulation (EC) No 1907/2006

DINITROL 445 Droehnex Black

Print date: 08.04.2016

Product code: 5104

Page 13 of 16

BCF

CAS No	Chemical name	BCF	Species	Source
1330-20-7	xylene	25,9	Oncorhynchus mykiss (Rainbow trout)	

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

not applicable

12.6. Other adverse effects

No information available.

Further information

There are no data available on the preparation/mixture itself.
Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Dispose of waste according to applicable legislation. Do not mix with other wastes.
List of proposed waste codes/waste designations in accordance with EWC:

Waste disposal number of waste from residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances
Classified as hazardous waste.

Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances
Classified as hazardous waste.

Contaminated packaging

Remove according to the regulations.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1139
14.2. UN proper shipping name: Coating solution
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Classification code: F1
 Special Provisions: 640D
 Limited quantity: 5 L
 Transport category: 2
 Hazard No: 33

Safety Data Sheet

according to Regulation (EC) No 1907/2006

DINITROL 445 Droehnex Black

Print date: 08.04.2016

Product code: 5104

Page 14 of 16

Tunnel restriction code: D/E

Other applicable information (land transport)

E2

Marine transport (IMDG)
14.1. UN number: UN 1139

14.2. UN proper shipping name: Coating solution

14.3. Transport hazard class(es): 3

14.4. Packing group: II

Hazard label: 3



Marine pollutant: no

Special Provisions: -

Limited quantity: 5 L

EmS: F-E, S-E

Other applicable information (marine transport)

E2

Air transport (ICAO)
14.1. UN number: UN 1139

14.2. UN proper shipping name: COATING SOLUTION (includes surface treatments or coatings used for industrial or other purposes such as vehicle under-coating, drum or barrel lining)

14.3. Transport hazard class(es): 3

14.4. Packing group: II

Hazard label: 3



Special Provisions: A3

Limited quantity Passenger: 1 L

IATA-packing instructions - Passenger: 353

IATA-max. quantity - Passenger: 5 L

IATA-packing instructions - Cargo: 364

IATA-max. quantity - Cargo: 60 L

Other applicable information (air transport)

E2

Passenger-LQ: Y341

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Warning: Flammable liquids

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Safety Data Sheet

according to Regulation (EC) No 1907/2006

DINITROL 445 Droehnex Black

Print date: 08.04.2016

Product code: 5104

Page 15 of 16

EU regulatory information

2004/42/EC (VOC): 43,6 % (510 g/l)
Subcategory according to Directive 2004/42/EC: Special finishes - All types, VOC limit value: 840 g/l

Additional information

Observe in addition any national regulations!
Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water contaminating class (D): 2 - water contaminating

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,2.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%

Relevant R phrases (number and full text)

10	Flammable.
11	Highly flammable.
20/21	Harmful by inhalation and in contact with skin.
36	Irritating to eyes.
38	Irritating to skin.
43	May cause sensitisation by skin contact.
48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
48/25	Toxic: danger of serious damage to health by prolonged exposure if swallowed.
51	Toxic to aquatic organisms.
52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
53	May cause long-term adverse effects in the aquatic environment.
63	Possible risk of harm to the unborn child.
65	Harmful: may cause lung damage if swallowed.
66	Repeated exposure may cause skin dryness or cracking.
67	Vapours may cause drowsiness and dizziness.

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
------	-------------------------------------

Safety Data Sheet

according to Regulation (EC) No 1907/2006

DINITROL 445 Droehnex Black

Print date: 08.04.2016

Product code: 5104

Page 16 of 16

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH208	Contains Fatty acids, C18-unsatd. , trimers, compds. with oleylamine, Fatty acids, tall-oil, compds. with oleylamine. May produce an allergic reaction.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)