

Safety Data Sheet

according to Regulation (EC) No 1907/2006

DINITROL 447 Protect Super Ligth Grey

Print date: 12.10.2015

Product code: 5101

Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

DINITROL 447 Protect Super Ligth Grey

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Anti-corrosive coating

1.3. Details of the supplier of the safety data sheet

Company name: DINOL GmbH

Street: Pyrmonter Strasse 76

Place: D-32676 Luegde

Telephone: +49 (0) 5281 9829 80

Telefax: +49 (0) 5281 9829 860

Responsible Department: msds@dinol.com

1.4. Emergency telephone

Giftnotruf Berlin: +49 30 30686 790 (Consultation in German and English)

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 2

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Highly flammable liquid and vapour.

Causes skin irritation.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazardous components which must be listed on the label

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

ethyl acetate

Hydrocarbons, C9, aromatics

Signal word: Danger

Pictograms:



Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

according to Regulation (EC) No 1907/2006

DINITROL 447 Protect Super Ligth Grey

Print date: 12.10.2015

Product code: 5101

Page 2 of 14

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves and eye/face protection.
P501	This material and its container must be disposed of as hazardous waste.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane			30 - < 35 %
	921-024-6	649-328-00-1	01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
1330-20-7	xylene			5 - < 10 %
	215-535-7	601-022-00-9	01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H226 H312 H332 H315 H319 H335 H373 H304			
141-78-6	ethyl acetate			5 - < 10 %
	205-500-4	607-022-00-5	01-2119475103-46	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
64742-95-6	Hydrocarbons, C9, aromatics			1 - < 3 %
	918-668-5	649-356-00-4	01-2119455851-35	
	Flam. Liq. 3, STOT SE 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H335 H336 H304 H411 EUH066			
100-41-4	ethylbenzene			1 - < 3 %
	202-849-4	601-023-00-4	01-2119892111-44	
	Flam. Liq. 2, Acute Tox. 4, STOT RE 2, Asp. Tox. 1; H225 H332 H373 H304			
7779-90-0	trizinc bis(orthophosphate)			0.1 - < 1 %
	231-944-3	030-011-00-6	01-2119485044-40	
	Aquatic Acute 1 (M-Factor = 10), Aquatic Chronic 1; H400 H410			

Full text of H and EUH statements: see section 16.

Further Information

Note: Each entry in the column EC number that begins with the number "9" is - until the publication the official registration number - one specified by ECHA provisional number for the substance. The above-mentioned substance(s) in this product is (are) identified by CAS number and indeed in Countries that are not subject to the REACH Regulation, or in a regulation which is not in accordance with new naming convention for hydrocarbons have been updated.

SECTION 4: First aid measures

4.1. Description of first aid measures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

DINITROL 447 Protect Super Ligth Grey

Print date: 12.10.2015

Product code: 5101

Page 3 of 14

General information

If unconscious place in recovery position and seek medical advice.
Never give anything by mouth to an unconscious person or a person with cramps.
In all cases of doubt, or when symptoms persist, seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

After contact with skin

Change contaminated clothing.
Wash with plenty of water/Soap.
If skin irritation occurs: Get medical advice/attention.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing. In case of eye irritation consult an ophthalmologist.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious).
Call a physician immediately.
Put victim at rest, cover with a blanket and keep warm.
Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Nausea, Drowsiness, Headache.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

alcohol resistant foam, Carbon dioxide (CO₂), Extinguishing powder, Water fog.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Danger of serious damage to health by prolonged exposure.
Do not inhale explosion and combustion gases. Use appropriate respiratory protection.

5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately.
Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Provide adequate ventilation.
Wear personal protection equipment.
Avoid contact with skin, eyes and clothes.
Avoid breathing dust/fume/gas/mist/vapours/spray.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Prevent spread over a wide area (e.g. by containment or oil barriers).

DINITROL 447 Protect Super Ligth Grey

Print date: 12.10.2015

Product code: 5101

Page 4 of 14

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Advice on protection against fire and explosion

Take precautionary measures against static discharges.

Keep away from sources of ignition. - No smoking.

Vapours are heavier than air and will spread at floor level.

Vapours may form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Keep container dry.

Keep away from heat. Protect against direct sunlight.

Advice on storage compatibility

Do not store together with: Oxidizing agents. Strong acid, strong alkalis

7.3. Specific end use(s)

Anti-corrosive coating

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
141-78-6	Ethyl acetate	200	-		TWA (8 h)	WEL
		400	-		STEL (15 min)	WEL
100-41-4	Ethylbenzene	100	441		TWA (8 h)	WEL
		125	552		STEL (15 min)	WEL
14807-96-6	Talc respirable dust	-	1		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid	650 mmol/mol	urine	Post shift

Safety Data Sheet

according to Regulation (EC) No 1907/2006

DINITROL 447 Protect Super Ligth Grey

Print date: 12.10.2015

Product code: 5101

Page 5 of 14

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
1330-20-7	xylene			
Worker DNEL, long-term		dermal	systemic	108 mg/kg bw/day
Worker DNEL, acute		inhalation	systemic	289 mg/m³
Worker DNEL, acute		inhalation	local	174 mg/m³
Worker DNEL, long-term		inhalation	systemic	77 mg/m³
Consumer DNEL, long-term		oral	systemic	1,6 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	108 mg/kg bw/day
Consumer DNEL, acute		inhalation	systemic	174 mg/m³
Consumer DNEL, acute		inhalation	local	174 mg/m³
Consumer DNEL, long-term		inhalation	systemic	14,8 mg/m³
,				
141-78-6	ethyl acetate			
Worker DNEL, long-term		inhalation	systemic	734 mg/m³
Worker DNEL, acute		inhalation	systemic	1468 mg/m³
Worker DNEL, long-term		inhalation	local	734 mg/m³
Worker DNEL, acute		inhalation	local	1468 mg/m³
Worker DNEL, long-term		dermal	systemic	63 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	367 mg/m³
Consumer DNEL, acute		inhalation	systemic	734 mg/m³
Consumer DNEL, long-term		dermal	systemic	37 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	4,5 mg/kg bw/day
100-41-4	ethylbenzene			
Worker DNEL, long-term		inhalation	systemic	77 mg/m³
Worker DNEL, acute		inhalation	local	293 mg/m³
Worker DNEL, long-term		dermal	systemic	180 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	15 mg/m³
Consumer DNEL, long-term		oral	systemic	1,6 mg/kg bw/day

DINITROL 447 Protect Super Ligth Grey

Print date: 12.10.2015

Product code: 5101

Page 6 of 14

PNEC values

CAS No	Substance	
Environmental compartment		Value
1330-20-7	xylene	
Freshwater		0,327 mg/l
Marine water		0,327 mg/l
Freshwater sediment		12,46 mg/kg
Marine sediment		12,46 mg/kg
Soil		2,31 mg/kg
Micro-organisms in sewage treatment plants (STP)		6,58 mg/l
141-78-6	ethyl acetate	
Freshwater		0,24 mg/l
Marine water		0,024 mg/l
Freshwater sediment		1,15 mg/kg
Marine sediment		0,115 mg/kg
Secondary poisoning		0,20 mg/kg
Micro-organisms in sewage treatment plants (STP)		650 mg/l
Soil		0,148 mg/kg
100-41-4	ethylbenzene	
Freshwater		0,1 mg/l
Marine water		0,01 mg/l
Freshwater sediment		13,7 mg/kg
Marine sediment		1,37 mg/kg
Secondary poisoning		0,02 mg/kg
Soil		2,68 mg/kg
Micro-organisms in sewage treatment plants (STP)		9,6 mg/l

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation.

If handled uncovered, arrangements with local exhaust ventilation should be used if possible.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Protective and hygiene measures

Keep away from food, drink and animal feedingstuffs.

When using do not eat or drink.

Wash hands before breaks and after work.

Avoid contact with skin and eyes.

Remove contaminated, saturated clothing immediately.

Do not breathe gas/vapour/aerosol.

Eye/face protection

Eye glasses with side protection (DIN EN 166)

DINITROL 447 Protect Super Ligth Grey

Print date: 12.10.2015

Product code: 5101

Page 7 of 14

Hand protection

Tested protective gloves must be worn (DIN EN 374):

FKM (fluoro rubber), Breakthrough time (maximum wearing time): 480 min.

PVA (Polyvinyl alcohol), Breakthrough time (maximum wearing time): 480 min.

NBR (Nitrile rubber), Breakthrough time (maximum wearing time): 30 min.

Butyl caoutchouc (butyl rubber) Breakthrough time (maximum wearing time):

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.
gas filtering equipment (EN 141)., Filter material/medium: A/P2

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	light grey
Odour:	characteristic

Test method

pH-Value:	not determined
-----------	----------------

Changes in the physical state

Melting point:	not determined
----------------	----------------

Initial boiling point and boiling range:	80 °C
--	-------

Flash point:	-5 °C DIN 51755
--------------	-----------------

Flammability

Solid:	not applicable
--------	----------------

Gas:	not applicable
------	----------------

Explosive properties

not determined

Lower explosion limits:	0,8 vol. %
-------------------------	------------

Upper explosion limits:	7,7 vol. %
-------------------------	------------

Ignition temperature:	200 °C
-----------------------	--------

Auto-ignition temperature

Solid:	not applicable
--------	----------------

Gas:	not applicable
------	----------------

Decomposition temperature:	not determined
----------------------------	----------------

Oxidizing properties

not determined

Vapour pressure: (at 20 °C)	61 hPa
--------------------------------	--------

Density (at 20 °C):	1,06 g/cm ³ ISO 2811
---------------------	---------------------------------

Water solubility:	insoluble
-------------------	-----------

Solubility in other solvents

not determined

Partition coefficient:	not determined
------------------------	----------------

Safety Data Sheet

according to Regulation (EC) No 1907/2006

DINITROL 447 Protect Super Ligth Grey

Print date: 12.10.2015

Product code: 5101

Page 8 of 14

Vapour density:	not determined
Evaporation rate:	not determined
Solvent separation test:	not determined
Solvent content:	52,00 %

9.2. Other information

Solid content:	48,00 %
----------------	---------

No information available.

SECTION 10: Stability and reactivity**10.1. Reactivity**

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from heat.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Carbon monoxide.

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

DINITROL 447 Protect Super Ligth Grey

Print date: 12.10.2015

Product code: 5101

Page 9 of 14

CAS No	Chemical name				
	Exposure routes	Method	Dose	Species	Source
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane				
	oral	LD50	>5000 mg/kg	Rat	
	dermal	LD50	>2000 mg/kg	Rat	
	inhalative (4 h) vapour	LC50	>20 mg/l	Rat	
1330-20-7	xylene				
	oral	LD50	4300 mg/kg	Rat	GESTIS
	dermal	LD50	>1700 mg/kg	Rabbit	GESTIS
	inhalative (4 h) vapour	LC50	21,7 mg/l	Rat	GESTIS
	inhalative aerosol	ATE	1,5 mg/l		
141-78-6	ethyl acetate				
	oral	LD50	4935 mg/kg	Rat	
	dermal	LD50	5000 mg/kg	Rabbit	
	inhalative (4 h) vapour	LC50	56 mg/l	Rat	
64742-95-6	Hydrocarbons, C9, aromatics				
	oral	LD50	3592 mg/kg	Rat	
	dermal	LD50	>3160 mg/kg	Rabbit	
	inhalative (4 h) vapour	LC50	6193 mg/l	Rat	
100-41-4	ethylbenzene				
	oral	LD50	3500 mg/kg	Rat	GESTIS
	dermal	LD50	15400 mg/kg	Rabbit	GESTIS
	inhalative (4 h) vapour	LC50	17,2 mg/l	Rat	
	inhalative aerosol	ATE	1,5 mg/l		
7779-90-0	trizinc bis(orthophosphate)				
	oral	LD50	> 5000 mg/kg	Rat	
	inhalative (4 h) aerosol	LC50	>5,7 mg/l	Rat	

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane), (ethyl acetate), (Hydrocarbons, C9, aromatics)

Severe effects after repeated or prolonged exposure

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Further information

There are no data available on the preparation/mixture itself.

according to Regulation (EC) No 1907/2006

DINITROL 447 Protect Super Ligth Grey

Print date: 12.10.2015

Product code: 5101

Page 10 of 14

SECTION 12: Ecological information

12.1. Toxicity

CAS No	Chemical name				
	Aquatic toxicity	Method	Dose	[h] [d]	Species
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane				
	Acute fish toxicity	LC50	11,4 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)
	Acute algae toxicity	ErC50	30 mg/l	72 h	Pseudokirchneriella subcapitata
	Acute crustacea toxicity	EC50	3 mg/l	48 h	Daphnia magna (Big water flea)
141-78-6	ethyl acetate				
	Acute fish toxicity	LC50	230 mg/l	96 h	Pimephales promelas (fathead minnow)
	Acute algae toxicity	ErC50	3300 mg/l		Desmodesmus subspicatus.
	Acute crustacea toxicity	EC50	717 mg/l	48 h	Daphnia magna (Big water flea)
	Acute bacteria toxicity		(2900 mg/l)		Pseudomonas putida
64742-95-6	Hydrocarbons, C9, aromatics				
	Acute fish toxicity	LC50	9,2 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)
	Acute algae toxicity	ErC50	2,9 mg/l	72 h	Pseudokirchneriella subcapitata
	Acute crustacea toxicity	EC50	3,2 mg/l	48 h	Daphnia magna (Big water flea)
7779-90-0	trizinc bis(orthophosphate)				
	Acute fish toxicity	LC50	0,09 mg/l	96 h	fish
					GESTIS

12.2. Persistence and degradability

There are no data available on the mixture itself.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
141-78-6	ethyl acetate			
	OECD 301D/ EEC 92/69/V, C.4-E	100 %	28	
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64742-49-0	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	3,4-5,2
1330-20-7	xylene	3
100-41-4	ethylbenzene	3,15

Safety Data Sheet

according to Regulation (EC) No 1907/2006

DINITROL 447 Protect Super Ligth Grey

Print date: 12.10.2015

Product code: 5101

Page 11 of 14

BCF

CAS No	Chemical name	BCF	Species	Source
1330-20-7	xylene	25,9	Oncorhynchus mykiss (Rainbow trout)	

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

not applicable

12.6. Other adverse effects

No information available.

Further information

There are no data available on the preparation/mixture itself.

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Dispose of waste according to applicable legislation. Do not mix with other wastes.

List of proposed waste codes/waste designations in accordance with EWC:

Waste disposal number of waste from residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances
Classified as hazardous waste.

Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances
Classified as hazardous waste.

Contaminated packaging

Remove according to the regulations.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:

UN 1139

14.2. UN proper shipping name:

Coating solution, ENVIRONMENTALLY HAZARDOUS

14.3. Transport hazard class(es):

3

14.4. Packing group:

II

Hazard label:

3



Classification code:

F1

Special Provisions:

640D

Limited quantity:

5 L

Transport category:

2

Safety Data Sheet

according to Regulation (EC) No 1907/2006

DINITROL 447 Protect Super Ligth Grey

Print date: 12.10.2015

Product code: 5101

Page 12 of 14

Hazard No: 33
Tunnel restriction code: D/E

Other applicable information (land transport)
E2

Marine transport (IMDG)

14.1. UN number: UN 1139
14.2. UN proper shipping name: COATING SOLUTION (Naphtha (petroleum), hydrotreated light, Solvent naphtha (petroleum), light arom.), MARINE POLLUTANT
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Marine pollutant: yes
Special Provisions: -
Limited quantity: 5 L
EmS: F-E, S-E

Other applicable information (marine transport)
E2

Air transport (ICAO)

14.1. UN number: UN 1139
14.2. UN proper shipping name: COATING SOLUTION
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Special Provisions: A3
Limited quantity Passenger: 1 L
IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

Other applicable information (air transport)
E2
Passenger-LQ: Y341

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes



Danger releasing substance: Naphtha (petroleum), hydrotreated light
trizinc bis(orthophosphate)

14.6. Special precautions for user

Warning: Flammable liquids

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Safety Data Sheet

according to Regulation (EC) No 1907/2006

DINITROL 447 Protect Super Ligth Grey

Print date: 12.10.2015

Product code: 5101

Page 13 of 14

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2004/42/EC (VOC): 52,0 % (540 g/l)

Additional information

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

National regulatory information

Employment restrictions: Observe employment restrictions for young people. Observe employment restrictions for child bearing mothers and nursing.

Water contaminating class (D): 2 - water contaminating

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Hydrocarbons, C9, aromatics

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,2.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

DINITROL 447 Protect Super Ligth Grey

Print date: 12.10.2015

Product code: 5101

Page 14 of 14

present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)