

Safety Data Sheet

according to Regulation (EC) No 1907/2006

DINITROL 8500 Grey Spray

Print date: 27.04.2016

Product code: 34054

Page 2 of 17

**Hazard statements**

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves and eye/face protection.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Special labelling of certain mixtures

EUH066	Repeated exposure may cause skin dryness or cracking.
--------	---

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

DINITROL 8500 Grey Spray

Print date: 27.04.2016

Product code: 34054

Page 3 of 17

Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification according to Directive 67/548/EEC	
Index No	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
REACH No		
200-662-2	acetone; propan-2-one; propanone	25-50 %
67-64-1	F - Highly flammable, Xi - Irritant R11-36-66-67	
606-001-00-8	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066	
01-2119471330-49		
200-827-9	propane	10-12,5 %
74-98-6	F+ - Extremely flammable R12	
601-003-00-5	Flam. Gas 1, Liquefied gas; H220 H280	
01-2119486944-21		
204-658-1	n-butyl acetate	10-12,5 %
123-86-4	R10-66-67	
607-025-00-1	Flam. Liq. 3, STOT SE 3; H226 H336 EUH066	
01-2119485493-29		
203-448-7	butane	5-10 %
106-97-8	F+ - Extremely flammable R12	
601-004-00-0	Flam. Gas 1, Liquefied gas; H220 H280	
01-2119474691-32		
203-603-9	2-methoxy-1-methylethyl acetate	5-10 %
108-65-6	R10	
607-195-00-7	Flam. Liq. 3; H226	
01-2119475791-29		
200-857-2	isobutane	5-10 %
75-28-5	F+ - Extremely flammable R12	
601-004-00-0	Flam. Gas 1, Liquefied gas; H220 H280	
200-751-6	butan-1-ol; n-butanol	2,5-5 %
71-36-3	Xn - Harmful, Xi - Irritant R10-22-37/38-41-67	
603-004-00-6	Flam. Liq. 3, Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, STOT SE 3, STOT SE 3; H226 H302 H315 H318 H335 H336	
01-2119484630-38		
231-944-3	trizinc bis(orthophosphate)	1-2,5 %
7779-90-0	N - Dangerous for the environment R50-53	
030-011-00-6	Aquatic Acute 1 (M-Factor = 10), Aquatic Chronic 1; H400 H410	
01-2119485044-40		
200-661-7	propan-2-ol; isopropyl alcohol; isopropanol	1-2,5 %
67-63-0	F - Highly flammable, Xi - Irritant R11-36-67	
603-117-00-0	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336	
01-2119457558-25		
	Nitrocellulose	1-2,5 %
9004-70-0	F - Highly flammable R11	
	Flam. Sol. 1; H228	

Full text of R, H and EUH phrases: see section 16.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

DINITROL 8500 Grey Spray

Print date: 27.04.2016

Product code: 34054

Page 4 of 17

Further Information

Note: Each entry in the column EC number that begins with the number "9" is - until the publication the official registration number - one specified by ECHA provisional number for the substance. The above-mentioned substance(s) in this product is (are) identified by CAS number and indeed in Countries that are not subject to the REACH Regulation, or in a regulation which is not in accordance with new naming convention for hydrocarbons have been updated.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

If unconscious place in recovery position and seek medical advice.

After contact with skin

If skin irritation occurs: Get medical advice/attention.

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of eye irritation consult an ophthalmologist.

After ingestion

Let water be drunken in little sips (dilution effect). Provide fresh air. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Nausea, Drowsiness, Headache.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO₂), Extinguishing powder, Water fog.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Danger of serious damage to health by prolonged exposure.

Do not inhale explosion and combustion gases. Use appropriate respiratory protection.

5.3. Advice for firefighters

Use water spray jet to protect personnel and to cool endangered containers.

Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wear personal protection equipment.

Avoid contact with skin, eyes and clothes.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

according to Regulation (EC) No 1907/2006

DINITROL 8500 Grey Spray

Print date: 27.04.2016

Product code: 34054

Page 5 of 17

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used.

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Advice on protection against fire and explosion

Take precautionary measures against static discharges.

Do not spray on naked flames or any incandescent material.

Keep away from sources of ignition. - No smoking.

Heating causes rise in pressure with risk of bursting.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Do not keep the container sealed. Keep container dry.

Keep in a cool, well-ventilated place.

Keep away from heat. Protect against direct sunlight.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
108-65-6	1-Methoxypropyl acetate	50	274		TWA (8 h)	WEL
		100	548		STEL (15 min)	WEL
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
71-36-3	Butan-1-ol	-	-		TWA (8 h)	WEL
		50	154		STEL (15 min)	WEL
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
123-86-4	Butyl acetate	150	724		TWA (8 h)	WEL
		200	966		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

Safety Data Sheet

according to Regulation (EC) No 1907/2006

DINITROL 8500 Grey Spray

Print date: 27.04.2016

Product code: 34054

Page 6 of 17

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
67-64-1	acetone; propan-2-one; propanone			
Worker DNEL, long-term		inhalation	systemic	1210 mg/m ³
Worker DNEL, acute		inhalation	local	2420 mg/m ³
Worker DNEL, long-term		dermal	systemic	186 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	200 mg/m ³
Consumer DNEL, long-term		dermal	systemic	62 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	62 mg/kg bw/day
123-86-4	n-butyl acetate			
Worker DNEL, long-term		inhalation	systemic	480 mg/m ³
Worker DNEL, acute		inhalation	systemic	960 mg/m ³
Worker DNEL, long-term		inhalation	local	480 mg/m ³
Worker DNEL, acute		inhalation	local	960 mg/m ³
Consumer DNEL, long-term		inhalation	systemic	102,34 mg/m ³
Consumer DNEL, acute		inhalation	systemic	859,7 mg/m ³
Consumer DNEL, long-term		inhalation	local	102,34 mg/m ³
Consumer DNEL, acute		inhalation	local	859,7 mg/m ³
108-65-6	2-methoxy-1-methylethyl acetate			
Worker DNEL, long-term		inhalation	systemic	275 mg/m ³
Worker DNEL, acute		inhalation	local	550 mg/m ³
Worker DNEL, long-term		dermal	systemic	796 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	33 mg/m ³
Consumer DNEL, acute		inhalation	local	33 mg/m ³
Consumer DNEL, long-term		dermal	systemic	320 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	36 mg/kg bw/day
71-36-3	butan-1-ol; n-butanol			
Worker DNEL, long-term		inhalation	local	310 mg/m ³
Consumer DNEL, long-term		oral	systemic	3,125 mg/kg bw/day
Consumer DNEL, long-term		inhalation	local	55 mg/m ³
7779-90-0	trizinc bis(orthophosphate)			
Worker DNEL, long-term		inhalation	systemic	5 mg/m ³
Worker DNEL, long-term		dermal	systemic	83 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	2,5 mg/m ³

Safety Data Sheet

according to Regulation (EC) No 1907/2006

DINITROL 8500 Grey Spray

Print date: 27.04.2016

Product code: 34054

Page 7 of 17

Consumer DNEL, long-term	dermal	systemic	83 mg/kg bw/day
Consumer DNEL, acute	oral	systemic	0,83 mg/kg bw/day
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol		
Consumer DNEL, long-term	inhalation	systemic	89 mg/m ³
Consumer DNEL, long-term	dermal	systemic	319 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	26 mg/kg bw/day

Safety Data Sheet

according to Regulation (EC) No 1907/2006

DINITROL 8500 Grey Spray

Print date: 27.04.2016

Product code: 34054

Page 8 of 17

PNEC values

CAS No	Substance	Value
Environmental compartment		
67-64-1	acetone; propan-2-one; propanone	
Freshwater		10,6 mg/l
Marine water		1,06 mg/l
Freshwater sediment		30,4 mg/kg
Marine sediment		3,04 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		29,5 mg/kg
123-86-4	n-butyl acetate	
Freshwater		0,18 mg/l
Marine water		0,018 mg/l
Micro-organisms in sewage treatment plants (STP)		35,6 mg/l
Freshwater sediment		0,981 mg/kg
Marine sediment		0,0981 mg/kg
Soil		0,0903 mg/kg
108-65-6	2-methoxy-1-methylethyl acetate	
Freshwater		0,635 mg/l
Marine water		0,0635 mg/l
Freshwater sediment		3,29 mg/kg
Marine sediment		0,329 mg/kg
Micro-organisms in sewage treatment plants (STP)		100 mg/l
Soil		0,290 mg/kg
71-36-3	butan-1-ol; n-butanol	
Freshwater		0,082 mg/l
Marine water		0,0082 mg/l
Freshwater sediment		0,178 mg/kg
Marine sediment		0,0178 mg/kg
Micro-organisms in sewage treatment plants (STP)		2476 mg/l
Soil		0,015 mg/kg
7779-90-0	trizinc bis(orthophosphate)	
Freshwater		0,0206 mg/l
Marine water		0,0061 mg/l
Micro-organisms in sewage treatment plants (STP)		0,100 mg/l
Freshwater sediment		117,8 mg/kg
Marine sediment		56,5 mg/kg
Soil		35,6 mg/kg
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	

Safety Data Sheet

according to Regulation (EC) No 1907/2006

DINITROL 8500 Grey Spray

Print date: 27.04.2016

Product code: 34054

Page 9 of 17

Freshwater	140,9 mg/l
Marine water	140,9 mg/l
Freshwater sediment	552 mg/kg
Marine sediment	552 mg/kg
Secondary poisoning	160 mg/kg
Micro-organisms in sewage treatment plants (STP)	2251 mg/l
Soil	28 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation.
 If handled uncovered, arrangements with local exhaust ventilation should be used if possible.
 If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Protective and hygiene measures

Keep away from food, drink and animal feedingstuffs.
 When using do not eat or drink.
 Wash hands before breaks and after work.
 Avoid contact with skin and eyes.
 Remove contaminated, saturated clothing immediately.
 Do not breathe gas/vapour/aerosol.

Eye/face protection

Eye glasses with side protection (DIN EN 166)

Hand protection

Tested protective gloves must be worn (DIN EN 374):
 Butyl caoutchouc (butyl rubber), Breakthrough time (maximum wearing time): 240 min.
 For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.
 Protective gloves have to be replaced at the first sign of deterioration.
 Protect skin by using skin protective cream.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

Work in well-ventilated zones or use proper respiratory protection.
 gas filtering equipment (EN 141), Filter material/medium: A/P2

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Aerosol
 Colour: grey
 Odour: characteristic

Test method

pH-Value: not determined

Changes in the physical state

Melting point: not determined
 Initial boiling point and boiling range: not applicable
 Flash point: < 0 °C

Safety Data Sheet

according to Regulation (EC) No 1907/2006

DINITROL 8500 Grey Spray

Print date: 27.04.2016

Product code: 34054

Page 10 of 17

Flammability

Solid:	not applicable
Gas:	not applicable

Explosive properties

not determined

Lower explosion limits:	1,2 vol. %
Upper explosion limits:	13,0 vol. %
Ignition temperature:	333 °C

Auto-ignition temperature

Solid:	not applicable
Gas:	not applicable

Decomposition temperature: not determined

Oxidizing properties

not determined

Vapour pressure: 3500 hPa
(at 20 °C)Density (at 20 °C): 0,78 g/cm³

Water solubility: insoluble

Solubility in other solvents

not determined

Partition coefficient: not determined

Viscosity / dynamic: not determined

Viscosity / kinematic: not determined

Vapour density: not determined

Evaporation rate: not applicable

Solvent separation test: not determined

Solvent content: 86,7 %

9.2. Other information

Solid content: 9,3 %

No information available.

SECTION 10: Stability and reactivity**10.1. Reactivity**

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from heat. Ignition hazard.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

Carbon monoxide.

according to Regulation (EC) No 1907/2006

DINITROL 8500 Grey Spray

Print date: 27.04.2016

Product code: 34054

Page 11 of 17

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Method	Dose	Species	Source
67-64-1	acetone; propan-2-one; propanone				
	oral	LD50	5800 mg/kg	Rat	RTECS
	dermal	LD50	20000 mg/kg	Rabbit	IUCLID
	inhalative (4 h) vapour	LC50	76 mg/l	Rat	
123-86-4	n-butyl acetate				
	oral	LD50	10760 mg/kg	Rat	
	dermal	LD50	14112 mg/kg	Rabbit	
	inhalative (4 h) aerosol	LC50	23,4 mg/l	Rat	
106-97-8	butane				
	inhalative (4 h) gas	LC50	273000 ppm	Rat	GESTIS
108-65-6	2-methoxy-1-methylethyl acetate				
	oral	LD50	8500 mg/kg	Rat	
	inhalative (4 h) vapour	LC50	35,7 mg/l	Rat	
71-36-3	butan-1-ol; n-butanol				
	oral	LD50	790 mg/kg	Rat	GESTIS
	dermal	LD50	3400 mg/kg	Rabbit	GSETIS
	inhalative (4 h) aerosol	LC50	>17 mg/l	Rat	
7779-90-0	trizinc bis(orthophosphate)				
	oral	LD50	> 5000 mg/kg	Rat	
	inhalative (4 h) aerosol	LC50	>5,7 mg/l	Rat	
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol				
	oral	LD50	4570 mg/kg	Rat	
	dermal	LD50	13400 mg/kg	Rabbit	
	inhalative (4 h) vapour	LC50	30 mg/l	Rat	

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (acetone; propan-2-one; propanone), (n-butyl acetate), (butan-1-ol; n-butanol), (propan-2-ol; isopropyl alcohol; isopropanol)

Severe effects after repeated or prolonged exposure

Repeated exposure may cause skin dryness or cracking.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

DINITROL 8500 Grey Spray

Print date: 27.04.2016

Product code: 34054

Page 12 of 17

Aspiration hazard

Based on available data, the classification criteria are not met.

Further information

There are no data available on the preparation/mixture itself.

SECTION 12: Ecological information

12.1. Toxicity

CAS No	Chemical name					
	Aquatic toxicity	Method	Dose	[h] [d]	Species	Source
67-64-1	acetone; propan-2-one; propanone					
	Acute fish toxicity	LC50	5540 mg/l	96 h	Onchorhynchus mykiss	
	Acute crustacea toxicity	EC50	8800 mg/l	48 h	Daphnia Magna	
	Algae toxicity	NOEC	4740 mg/l	2 d	Selenastrum capricornutum	
123-86-4	n-butyl acetate					
	Acute fish toxicity	LC50	18 mg/l	96 h	Pimephales promelas (fathead minnow)	
	Acute algae toxicity	ErC50	647,7 mg/l	72 h	Desmodesmus subspicatus.	
	Acute crustacea toxicity	EC50	44 mg/l	48 h	Daphnia magna (Big water flea)	
	Algae toxicity	NOEC	200 mg/l		Desmodesmus subspicatus.	
108-65-6	2-methoxy-1-methylethyl acetate					
	Acute fish toxicity	LC50	100-180 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute crustacea toxicity	EC50	>500 mg/l	48 h	Daphnia magna (Big water flea)	
71-36-3	butan-1-ol; n-butanol					
	Acute fish toxicity	LC50	1740 mg/l	96 h	Pimephales promelas (fathead minnow)	
	Acute algae toxicity	ErC50	>500 mg/l	72 h	Scenedesmus subspicatus	
	Acute crustacea toxicity	EC50	1980 mg/l	48 h		GESTIS
	Acute bacteria toxicity		(2250 mg/l)		Pseudomonas putida	16 h
7779-90-0	trizinc bis(orthophosphate)					
	Acute fish toxicity	LC50	0,09 mg/l	96 h	fish	GESTIS
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol					
	Acute fish toxicity	LC50	>100 mg/l	96 h	fish	
	Acute algae toxicity	ErC50	>100 mg/l			
	Acute crustacea toxicity	EC50	>100 mg/l	48 h	Daphnia magna (Big water flea)	

12.2. Persistence and degradability

There are no data available on the mixture itself.

according to Regulation (EC) No 1907/2006

DINITROL 8500 Grey Spray

Print date: 27.04.2016

Product code: 34054

Page 13 of 17

CAS No	Chemical name	Method	Value	d	Source
		Evaluation			
67-64-1	acetone; propan-2-one; propanone				
		OECD 301 B	91%	28	
	Readily biodegradable (according to OECD criteria).				
123-86-4	n-butyl acetate				
		OECD 301D/ EEC 92/69/V, C.4-E	83%	28	
	Readily biodegradable (according to OECD criteria).				
108-65-6	2-methoxy-1-methylethyl acetate				
		OECD 302 B	>90 %		
	Readily biodegradable (according to OECD criteria).				

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-64-1	acetone; propan-2-one; propanone	-0,24
74-98-6	propane	2,36
123-86-4	n-butyl acetate	2,3
106-97-8	butane	2,89
108-65-6	2-methoxy-1-methylethyl acetate	0,56
75-28-5	isobutane	2,8
71-36-3	butan-1-ol; n-butanol	0,88
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	-0,16
9004-70-0	Nitrocellulose	<0

BCF

CAS No	Chemical name	BCF	Species	Source
67-64-1	acetone; propan-2-one; propanone	<10		

12.4. Mobility in soil

There are no data available on the mixture itself.

12.5. Results of PBT and vPvB assessment

not applicable

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations
13.1. Waste treatment methods
Advice on disposal

Dispose of waste according to applicable legislation. Do not mix with other wastes.

List of proposed waste codes/waste designations in accordance with EWC:

Waste disposal number of waste from residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances
Classified as hazardous waste.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

DINITROL 8500 Grey Spray

Print date: 27.04.2016

Product code: 34054

Page 14 of 17

Waste disposal number of used product

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances
Classified as hazardous waste.

Waste disposal number of contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances
Classified as hazardous waste.

Contaminated packaging

Remove according to the regulations.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
 Hazard label: 2.1



Classification code: 5F
 Special Provisions: 190 327 344 625
 Limited quantity: 1 L
 Excepted quantity: E0
 Transport category: 2
 Tunnel restriction code: D

Marine transport (IMDG)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
 Hazard label: 2.1



Marine pollutant: no
 Special Provisions: 63, 190, 277, 327, 344, 959
 Limited quantity: 1000 mL
 Excepted quantity: E0
 EmS: F-D, S-U

Air transport (ICAO)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS

Safety Data Sheet

according to Regulation (EC) No 1907/2006

DINITROL 8500 Grey Spray

Print date: 27.04.2016

Product code: 34054

Page 15 of 17

14.3. Transport hazard class(es): 2.1

14.4. Packing group: -

Hazard label: 2.1



Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G

Passenger LQ: Y203

Excepted quantity: E0

IATA-packing instructions - Passenger: 203

IATA-max. quantity - Passenger: 75 kg

IATA-packing instructions - Cargo: 203

IATA-max. quantity - Cargo: 150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Warning: Gases under pressure

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

Other applicable information

Stowage Code:

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

Segregation Code:

SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2004/42/EC (VOC): 86,7 % (676 g/l)

Subcategory according to Directive 2004/42/EC: Special finishes - All types, VOC limit value: 840 g/l

Additional information

Observe in addition any national regulations!

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water contaminating class (D): 1 - slightly water contaminating

Safety Data Sheet

according to Regulation (EC) No 1907/2006

DINITROL 8500 Grey Spray

Print date: 27.04.2016

Product code: 34054

Page 16 of 17

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,3,7,9,14,15.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Relevant R phrases (number and full text)

10	Flammable.
11	Highly flammable.
12	Extremely flammable.
22	Harmful if swallowed.
36	Irritating to eyes.
37/38	Irritating to respiratory system and skin.
41	Risk of serious damage to eyes.
50	Very toxic to aquatic organisms.
51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
53	May cause long-term adverse effects in the aquatic environment.
66	Repeated exposure may cause skin dryness or cracking.
67	Vapours may cause drowsiness and dizziness.

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H228	Flammable solid.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other



Safety Data Sheet

according to Regulation (EC) No 1907/2006

DINITROL 8500 Grey Spray

Print date: 27.04.2016

Product code: 34054

Page 17 of 17

products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)