

Printing date 28.07.2015 Version number 12 Revision: 28.07.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: DINITROL ML
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Anticorrosion additive
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

DINOL GmbH
Pyrmonter Str. 76
D-32676 Lügde
Tel: +49 5281 9829 80

Fax: +49 5281 9829 860 E-mail: msds@dinol.com

- · Further information obtainable from: Research & Development
- · 1.4 Emergency telephone number:

Giftnotruf Berlin +49(0)30 30686 790 Beratung in Deutsch und Englisch.

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS07

- · Signal word Warning
- · Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated heavy Naphtha (petroleum), hydrotreated heavy

· Hazard statements

H226 Flammable liquid and vapour. H336 May cause drowsiness or dizziness.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Take precautionary measures against static discharge.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

(Contd. on page 2)



Printing date 28.07.2015 Version number 12 Revision: 28.07.2015

Trade name: DINITROL ML

(Contd. of page 1)

P501

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains Calcium Sulfonate. May produce an allergic reaction.

· 2.3 Other hazards

The petroleum naphtha / petroleum distillate / lubricating oil meet the requirements for not being classified as carcinogenic (<0,1% benzene alt<3% (w/w) DMSO extract (IP 346)).

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with additions.

· Dangerous components:		
CAS: 64742-48-9	Naphtha (petroleum), hydrotreated heavy	25-<50%
EC number: 919-857-5	♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ STOT SE 3, H336	
Reg.nr.: 01-2119463258-33	· · · · · · · · · · · · · · · · · · ·	
CAS: 64742-48-9	Naphtha (petroleum), hydrotreated heavy	1-<5%
EINECS: 265-150-3	🚸 Flam. Liq. 3, H226; 🗞 Asp. Tox. 1, H304; 🕠 STOT SE 3, H336	
CAS: 61789-86-4	Calcium Sulfonate	1-<5%
	🔥 Skin Sens. 1B, H317	

[·] Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Seek medical treatment.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- \cdot 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Mount respiratory protective device.
- · Additional information Cool endangered receptacles with water spray.

GB



Printing date 28.07.2015 Version number 12 Revision: 28.07.2015

Trade name: DINITROL ML

(Contd. of page 2)

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Avoid contact with skin, eyes and clothes.

- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Use only in well ventilated areas.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

DNELs		
64742-48-	9 Naphtha (petroleum), hydrotreated heavy	
Oral	Long-term - systemic effects, general population	125 mg/kg bw/day (General Population)
Dermal	Long-term - systemic effects, general population	125 mg/kg bw/day (General population)
	Long-term - systemic effects, worker	208 mg/kg bw/day (Worker)
Inhalative	Long-term - systemic effects, general population	185 mg/m3 (General Population)
	Long-term - systemic effects, worker	871 mg/m3 (Worker)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

• **Respiratory protection:** Suitable respiratory protective device recommended.

(Contd. on page 4)

(Contd. of page 3)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.07.2015 Version number 12 Revision: 28.07.2015

Trade name: DINITROL ML

· Protection of hands:



· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber

Recommended thickness of the material: ≥ 0.12 *mm*

· Penetration time of glove material

 $> 480 \, min$

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Upper:

· Density At 20 °C:

· Relative density

Vapour densityEvaporation rate

· Vapour pressure At 20 °C:

Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information	
· Appearance:	** **
Form:	Liquid
Colour:	Brown
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	130 °C
· Flash point:	40 °C (DIN 53213)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	> 200 °C
Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapou mixtures are possible.
· Explosion limits:	
Lower:	0.6 Vol %

7.0 Vol %

0.86 g/cm³ (DIN 51757) Not determined.

Not determined.

Not determined.

3 hPa

(Contd. on page 5)



Printing date 28.07.2015 Version number 12 Revision: 28.07.2015

Trade name: DINITROL ML

		(Contd. of page
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/w	ater): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic At 20 °C:	60 s (DIN 53211/4)	
· Solvent content:		
Organic solvents:	52.5 %	
Solids content:	47.5 % (DIN 53216)	
· 9.2 Other information	No further relevant information available.	
· VOC (EU):	52.48 %	
· VOC (EU):	451.3 g/l	
· VOCV:	52.48 %	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

· LD/LC50 1	· LD/LC50 values relevant for classification:		
64742-48-	64742-48-9 Naphtha (petroleum), hydrotreated heavy		
Oral	LD50	>5000 mg/kg (RAT)	
Dermal	LD50	>5000 mg/kg (RABBIT)	
Inhalative	LC50/4 h	> 4951 mg/l (RAT)	
64742-48-	64742-48-9 Naphtha (petroleum), hydrotreated heavy		
Oral	LD50	>5000 mg/kg (RAT)	
Dermal	LD50	>3000 mg/kg (RAT)	
. Primary ir	. Primary irritant offact		

- · Primary irritant effect:
- · Skin corrosion/irritation

Prolonged or repeated contact with skin may cause slight irritation and/or reddening.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information: No further relevant information available.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

· STOT-repeated exposure Based on available data, the classification criteria are not met.

(Contd. on page 6)



Printing date 28.07.2015 Version number 12 Revision: 28.07.2015

Trade name: DINITROL ML

(Contd. of page 5)

· Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Dispose of as dangerous waste.

· European	waste catalogue
08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

- · 14.1 UN-Number
- · ADR, IMDG, IATA UN1139
- · 14.2 UN proper shipping name
- · ADR 1139 COATING SOLUTION, special provision 640E
- · IMDG, IATA COATING SOLUTION
- · 14.3 Transport hazard class(es)
- · ADR, IMDG, IATA



· Class 3 Flammable liquids.

· Label

(Contd. on page 7)



Printing date 28.07.2015 *Version number* 12 *Revision:* 28.07.2015

Trade name: DINITROL ML

	(Contd. of page
14.4 Packing group	
ADR, IMDG, IATA	III
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	30
EMS Number:	F-E, <u>S-E</u>
14.7 Transport in bulk according to Ann	nex II of
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
· · · ~	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN1139, COATING SOLUTION, special provision 640

SECTION 15: Regulatory information

- \cdot 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02

GHS07

- · Signal word Warning
- · Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated heavy Naphtha (petroleum), hydrotreated heavy

· Hazard statements

H226 Flammable liquid and vapour. H336 May cause drowsiness or dizziness.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P243 Take precautionary measures against static discharge.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

(Contd. on page 8)



Printing date 28.07.2015 *Version number* 12 *Revision:* 28.07.2015

Trade name: DINITROL ML

(Contd. of page 7)

P501

Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · National regulations:
- · Technical instructions (air):

Class	Share in %
NK	52.5

- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

- · Department issuing MSDS: Research & Development
- · Contact: Kontakt: msds@dinol.com oder Tel.: 0049 (0)5281 982 980
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

 $DNEL: Derived\ No\text{-}Effect\ Level\ (REACH)$

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Skin Sens. 1B: Sensitisation - Skin, Hazard Category 1B

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

* * Data compared to the previous version altered.

GB