

DINITROL 447

Protect Super Spray

Characteristics:

DINITROL 447 Protect Super Spray is a quick-drying bodywork protection product with a rubber-synthetic resin base. Zinc additives enable significantly higher rust protection. Zinc ions prevent or delay the formation of rust on areas where the protective film has been damaged.

DINITROL 447 Protect Super Spray is free from aggressive solvents, and is particularly suitable for post-treatment protection on vehicle bodywork.

DINITROL 447 Protect Super Spray is not harmful to PVC films, and is permanently elastic and resistant to stone chippings and road salt. Once completely dry, DINITROL 447 Protect Super Spray can be coated with all standard lacquers.

Application:

As corrosion protection on the bodywork rear side, as protection against stone chippings on front and rear valances, to improve damaged, but healthy underbody protective films. Good compatibility with cleaning films and asphalt underbody protective types with bitumen or high oil content.

Method of use:

The surface to be treated must be dry and free from dust, oil and grease. Loose old coats must be removed. Remove severe rust with a steel wire brush. Shake the can well before use. Spray the material in an even cross coat at a distance of approx. 30 cm. If applying thicker layers, allow to air between coats. For larger surfaces or longer spraying procedures, the can should be shaken well in between. The material can be coated once dry.

Technical properties:

Colour:	black
Base:	synthetic resin / rubber
Density:	0.82 g/cm ³
Flash point:	- 20°C
Propellant:	Propane/butane
Recommended film thickness wet:	1700 µm
Package size:	500 ml spray
Storage time:	between 15°C and 25°C 24 months

Please refer to the safety data sheet or packaging label for safety instructions.

Die in diesem Merkblatt gemachten Angaben sind das Ergebnis sorgfältiger Untersuchungen. Soweit sie sich auf die Anwendung beziehen, sind sie als Empfehlung zu betrachten, die dem Erfahrungsstand entsprechen. Wegen der Vielseitigkeit der Anwendungs- und Arbeitsweisen können wir jedoch eine Verbindlichkeit nicht übernehmen. Es wird daher ein vertragliches Rechtsverhältnis nicht begründet, und es entstehen aus eventuellen Kaufverträgen keine Nebenverpflichtungen.

All data and recommendations are the result of careful tests by our laboratories. They only can be considered as recommendation which correspond to the level of experience of today. The data are given in good faith. However, in view of the multiplicity of possible application and working methods we are not in a position to assume any responsibility or obligations deriving from the use of our products.

DINOL GmbH
Pyrmonter Str. 76
D-32676 Lügde
Telefon:
+49 (0) 52 81 / 9 82 98-0
Telefax:
+49 (0) 52 81 / 9 82 98-60
E-Mail:
service@dinol.com